

Stationary thermal screening

Stationary, which shows the temperature in motion on several moving objects at the same time (does not require standing on the ground), with an accuracy of 0.3 degrees (installation)

N	Description	Imagery	U/Price	Q-ty	T/Price
1	Hikvision DS-2TD2617B-3/PA Thermal : 160 × 120 ; Lens: 3mm ; FOV : 50°×37.2°; Optical : 2688 × 1520 ; Lens: 4mm ; Video mode : Bi-spectrum image fusion ; Accuracy : ±0.5°C (±0.3° with black body)		USD 4,710.00	1	USD 4,710.00
2	Hikvision DS-2TE127-G4A Temperature range: 5~50°C. Temperature resolution: 0.1°C. Accuracy: ±0.1°C. Temperature stability: ±0.1°C/h Effective emissivity: 0.97±0.02 Operating temperature: 0~40°C Power : AC 110V~220V		USD 3,590.00	1	USD 3,590.00
3	Camera and temperature standard stand set * Camera and temperature standard stand * Bullet camera mount bracket * Temperature Etalon Reinforcing Cronstein		USD 210.00	2	USD 420.00
4	DS-3E0105P-E(B) 4 x 100M PoE IEEE802.3at/af ports and 1 x 100M Ethernet port. Supports 8-core power supply. Up to 250 m transmission distance.		USD 39.00	1	USD 39.00
5	Set of connecting cables				USD 112.50
6	Installation				USD 250.00
Total Price (inc VAT)					USD 9,121.50

Stationary thermal screening

Stationary which shows the temperature in motion, on several moving objects simultaneously (does not require standing on the ground), with an accuracy of 0.5 degrees (installation)

N	Description	Imagery	U/Price	Q-ty	T/Price
1	Hikvision DS-2TD2617B-3/PA Thermal : 160 × 120 ; Lens: 3mm ; FOV : 50°×37.2°; Optical : 2688 × 1520 ; Lens: 4mm ; Video mode : Bi-spectrum image fusion ; Accuracy : ±0.5°C (±0.3° with black body)		USD 4,710.00	1	USD 4,710.00
2	Camera and temperature standard stand set * Camera and temperature standard stand * Bullet camera mount bracket * Temperature Etalon Reinforcing Cronstein		USD 210.00	1	USD 210.00
3	DS-3E0105P-E(B) 4 x 100M PoE IEEE802.3at/af ports and 1 x 100M Ethernet port. Supports 8-core power supply. Up to 250 m transmission distance.		USD 39.00	1	USD 39.00
4	Set of connecting cables				USD 112.50
5	Installation				USD 250.00
Total Price (inc VAT)					USD 5,321.50

Mobile thermal screening

N	Description	Imagery	U/Price	Q-ty	T/Price
Handheld Thermal Camera - (Extra Camera) - Temperature Distance Up to 1.5-2.0 Meters					
1	Hikvision DS-2TP21B-6AVF/W Thermal : 160 × 120, 6.2mm, 25°× 19° Visible : 2MP Bi-spectrum image fusion ; WiFi, Audio alarm Accuracy : ±0.5°C Range : 30-45°C Working temperature : 10~35°C IP54 Installation height : 1.5m Face distance : 1.5~2.5m				USD 3,600.00
Handheld Thermal Camera - (Extra Camera) - Temperature Distance Up to 1 Meters					
2	Hikvision DS-2TP31B-3AUF Thermal : 160 × 120 ; Accuracy : ±0.5°C Range : 30-45°C Working temperature : 10~35°C Installation height : 1.5m Face distance : 1.0m				USD 1,285.00