

TTAF ELECTRONIC MANUFACTORY CO.,LTD

Flat/RM N BLK2 17/F Goldfield Building 144-150

Tai Lin Pai Road,

Kwai Chung , Hong Kong

Tel:(852) 27568101 Fax: (852) 27568202

Register No: 1014315

e-mail: info@ttaf.com.tr Web: www.ttaf.com.tr , www.ttaf.com

	Product	Technical data	Photo	Capacity/ Monthly (pcs)	Certificate	Price USD/pcs -TTAF
1	Coronavirus Disease 2019 Antibody (IgG/IgM) Combined Test Kits for Detecting Novel Coronavirus COVID-19 (Sars-CoV-2) IgG / AmG Antibody Test			40 000 000	FDA	\$13.00
2	Protective mask KN95	Classification: 9001 FFP2 NR D		40 000 000	FDA	\$3.00
3	Masks 3M 8210 Masks 3M 1860	Health Care Particulate Respirator and Surgical Mask		30 000 000	FDA	\$11.00
4	Protective plastic face shield.			1 000 000	CE	\$2.40
5	Protective clothing (overalls)	1. Elasticated hood and self-adhesive chin flap 2. Stitched and overtaped seams 3. Elasticated cuff and ankles 4. Zipper with self-adhesive double zip flap 5. Thumb loop (For safety reasons, the use of thumb loops is only recommended when double gloves are worn)		10 000 000	CE	\$20.00
6	Infrared Thermometer			200 000	FDA	\$50.00

7	TT7F-5	Oxygen flow: 0.5-5L/min Oxygen concentration: 95.5%-87% Pressure relief mechanism operational at: 250kPa±25kPa Operation noise level: <53dB(A) Input power: 500VA Minimum operating time: 30 minutes		10 000	FDA	\$720.00
8	TT7F-5 Double Flux	with cord controller		10 000	FDA	\$780.00
9	TT7F-5 Mini	More portable and takes up less space. Maximum Nebulizing Rate of 3L: >0.15mL/min Maximum Nebulizing Rate of 5L: >0.2mL/min		10 000	FDA	\$685.00
10	TT9F-3AW	Oxygen Flow range: 0.5-3L/min Oxygen concentration: 93%±3% Output pressure: 20kPa-50kPa Input power: 320VA N.W.: 16.5kg Operation noise level: <46dB(A) Size: 50*21 *64cm		10 000	CE	\$750.00
11	TT7F-8	Oxygen Flow range: 0.5-8L/min Oxygen concentration: 95.5%-87% Pressure relief mechanism operational at: 250kPa±25kPa Operation noise level: <55dB(A) Input power: 500VA		10 000	CE	\$1,090.00

12	TT7F-10	Oxygen Flow range: 0.5-10L/min Oxygen concentration: 95.5%-87% Output pressure: 40-70kPa Pressure relief mechanism operational at: 250kPa±25kPa Operation noise level: <60dB(A) Input power: 850VA Minimum operating time: 30 minutes it is also used for hospitals		10 000	CE	\$1,280.00
13	TT300	Oxygen Flow range: 1-5L/min Oxygen concentration: 30%-90% Output pressure: 20kPa-50kPa Input power: 100VA N.W.: 7.5kg Operation noise level: 43dB(A) Size: 27*17.5*29.5cm		10 000	CE	\$525.00
14	VOLANS UV-A	50 cm on/ off button			CE	\$125.00
15	VOLANS UV-A	50 cm with tripod		CE	CE	\$140.00
16	VOLANS UV-A	100 cm with screw and magnet		CE	CE	\$155.00
17	VOLANS UV-A	100 cm ceiling hanging ropes		CE	CE	\$180.00
18	VOLANS UV-A	200 cm with screw and magnet		CE	CE	\$295.00
19	VOLANS UV-A	200 cm ceiling hanging ropes		CE	CE	\$280.00
20	VOLANS UV-A	300 cm with screw and magnet		CE	CE	\$380.00
21	VOLANS UV-A	300 cm ceiling hanging ropes		CE	CE	\$350.00
22	ESL20 UV-C	Power Consumption: 70W Operating Factor: > 0,9 Input Surge Protection: 6kV Line-Line, 10kV Line-Earth Electrical Isolation Class: Class 1 Color Temperature: UV-C (265-285 nm) Light Source: SMD LED LED Life Time: >8000 hours LED Quantity: 140 pcs Body: Aluminium Injection Dimensions: 535 x 295 x 250 mm		CE	CE	\$6,200.00